

DIMENSION TABLE (MODEL WITHOUT BRAKE)

MODEL	LL	LR	LS	LW	S	LV	U	TAPER	WK	W	T	RH	TP	LP	LE
ECMA-C□0602ES	105.5	30	24	20	14	—	—	—	5	5	5	11	—	300	300
ECMA-C□0602GS	105.5	30	24	20	14	—	—	—	5	5	5	11	—	300	300
ECMA-C□0602AS	105.5	30	24	—	14	—	—	—	5	5	5	—	—	300	300
ECMA-C□0602EC	105.5	30	24	20	14	—	—	—	5	5	5	11	—	3000	3000



KEY DETAILS



SHAFT END DETAILS



ALTERNATIVE SHAFT KEYWAY TYPE



ENCODER CONNECTION			
PIN No.	FUNCTION 2500ppr	FUNCTION 20bit	COLOR
1	A	T+	BLK
2	B	BAT_5V	WHT
3	Z		ORG
4	Ā	T-	BLK/RED
5	B̄	BAT_GND	WHT/RED
6	Z̄		ORG/RED
7	DC+5V	DC+5V	BRN
8	GND	GND	BLU
9	SHIELD	SHIELD	SHIELD



MOTOR CONNECTION		
PIN No.	FUNCTION	COLOR
1	U	RED
2	V	WHT
3	W	BLK
4	GND	GRN/YEL



ENCODER CONNECTION (D-SUB TYPE)		
PIN No.	FUNCTION	COLOR
1	Z̄	ORG/RED
2	B̄	WHT/RED
3	B	WHT
4	A	BLK
5	Ā	BLK/RED
6	GND	BLU
7	GND	BLU
8	DC+5V	BRN
9	Z	ORG
—	SHIELD	SHIELD

REV.	ECN NO.
V1.0	

台達電子工業股份有限公司
DELTA ELECTRONICS, INC.

Drawn: | Design:
Date: | ECN No.:

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUSES OR DEVICES WITHOUT PERMISSION.

DIMENSIONAL TOLERANCES

( )		( )		( )		( )		ANGLES	
DECIMALS	<50	:±0.1	<50	:±0.15	<50	:±0.2	<30°	:±0.1°
X	:±0.3	>50~100	:±0.15	>50~100	:±0.2	>50~100	:±0.25	30°~60°	:±0.3°
X.X	:±0.2	>100~200	:±0.2	>100~200	:±0.25	>100~200	:±0.3	60°~90°	:±0.5°
X.XX	:±0.1	200~	:±0.2%	200~	:±0.25%	200~	:±0.3%		

Drawing Name: ECMA-C□0602□S | A3 SIZE | THIRD ANGLE PROJECTION | Part No.: | REV. V1.0

USED ON XXXXXX | UNIT mm | SCALE ------ | SHEET 1 OF 1

DF-MEA3H-3R00